



JA-123E-NFC Bus outdoor keypad with RFID reader 13.56 Mhz

The RFID card reader and keypad can be used for the **activation of a PG output by which you can control access to an area by, for example, an electric lock or a security system.**

Description

The module has a reading part, control segment and optical system for status indication.

Technical specifications

Power supply	from the control panel bus, 12 V DC (8-15 V)
Rated current consumption	15 mA
Maximum current consumption	80 mA
Type of control device	B
Operating frequency	13,56 MHz
Max. RFID mag. field strength	10,37 dBuA/m (3 m)
Compatible RFID cards	NFC, Mifare® Classic, Mifare® DESFire® 4, 7 Byte UID
Dimensions	46 x 151,5 x 25 mm
Weight	196 g
Connection cable length	3,0 m
Operaing temperature range	-25 °C to +60 °C
Relative humidity	75% non-condensing
Environment according to EN 50131-1	IV. outdoor general
Classification	grade 2 according to EN 50131-1, EN 50131-3
Also complies with	ETSI EN 300 330, EN 50130-4, EN 55032, EN 62368-1, EN IEC 63000

Recommended screw

3 x  \varnothing 3.5 x 40 mm (half-round head)

MIFARE® is a registered trademark of NXP B.V. NXP B.V. and Jablotron Alarms a.s. are not affiliated.